



Silo de carga a granel fabricado en acero de alta resistencia S350GD con galvanizado Z-600 (600 gr/m²) y refuerzos verticales atornillados de manera exterior.

Bulk Load Silo manufactured in corrugated panels of high strength steel S350 GD with galvanization Z-600 (600 gr/m²) and vertical stiffeners screwed outside.

Uniones totalmente atornilladas con tornillería bicromatada 8.8 y arandelas de goma.

Completely bolted unions with 8.8 bicromated bolts&nuts with rubber washers.

Soporte de estructura metálica y refuerzos galvanizados en caliente Z-600 (600 gr/m²).

Supported by metallic structure of hot deep galvanized Z-600 (600 gr/m²) with reinforcements.

Masilla BSD compuesta para el sellado de las uniones de los paneles y para la union del cilindro con el cono.

Mastic BSD compound for sealing panel unions and for cylinder with cone.

Placas de fijación con tornillo/taco de fijacion al suelo.

Fixation plates and fasteners to ground.

Escalera de acceso a techo con protección de acuerdo a UNE-EN-ISO 14122 como opcional.

Access ladder to roof with protection according to UNE-EN-ISO 14122 as optional.

CILINDER HEIGHT (m)		A					
TOTAL HEIGHT (m)		B					
▲ Intermediate capacities available							
BULK LOAD SILOS							
CAPACITY (m ³)							
11,5 ▲ 21,9 ▲ 23,9 ▲ 38 ▲ 56,8 ▲ 69,1 ▲ 127							
DIAMETER (m)	2,55	1,14 8,78	3,43 11,06	6,86 14,5	56,8	69,1	127
	3,50		1,14 9,37		4,58 12,8		
	4,65					1,14 10,93	5,72 14,36



Diseños y modelos disponibles para necesidades especiales



Special feautres or model available under request